



TIKKURILA

MUTE

DEEP MATT INTERIOR PAINT

DESCRIPTION

Tikkurila Mute is a deep matt interior paint for walls and ceiling.

RECOMMENDED USES

Suitable for the interior painting of plaster, concrete, filler-treated, brick, cardboard, wood surfaces, cardboard-covered plasterboard, chipboard and wood fiberboard. Suitable for both new and previously painted surfaces.

PRODUCT FEATURES

The paint is easy to apply due to the product's superior formula composition. Achieving a smooth, even surface requires minimal effort. The deep matt finish ensures a streak-free, uniform appearance. Additionally, the paint can be tinted in a variety of shades from the Tikkurila color selection, with particularly appealing results achieved using strong colours.



The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

MUTE

TECHNICAL DATA	
Base paints	AB1 BASE, C BASE
Colour Shades	Color cards: Mute, Symphony Color System, Deco Grey colour card Can be tinted in Tikkurila colors.
Gloss	Full matt. 6/RT - classification
Coverage	Theoretical coverage 8-12 m ² /l. Practical coverage depends on the application method, conditions, shape and roughness of the surface to be treated.
Can sizes	AB1 BASE: 0.18 l, 0.9 l, 2.3 l, 4.6 l C BASE: 0.18 l, 0.9 l, 2.3 l, 4.6 l
Thinner	Water
Application method	Brush, roller or spray. Airless spraying – nozzle 0.016"–0.018" – thinning 0–10% by volume.
Drying time	Dust dry after 30 minutes. Recoatable after 1-2 hours.
Density (kg/l)	Approx. 1.3 kg/l depending on shade, ISO 2811.
Chemical resistance	Resistant to cleaning with mild detergents.
Wet scrub resistance	SFS-EN 13300 class I, ISO 11998.
Volume solids (%)	40
VOC	Mute contains less than 2g/l VOC.
Storage	Protect from frost. Badly closed or short cans and/or tinted products do not withstand long storage. Tinted products should be used during the same painting season.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

MUTE

APPLICATION INSTRUCTIONS

Application conditions

The surface to be painted must be dry, the ambient temperature at least +5 °C and the relative humidity of air below 80%.

Surface preparation

Unpainted surfaces:

Clean the new surfaces by removing any dirt and dust. If necessary, level the surfaces with a suitable Presto filler and sand the dried surface. Remove the sanding dust. Prime the surface with Varma primer, for example.

Previously painted surfaces:

Wash surfaces with Seinäpesu detergent. Sand the painted surfaces non-glossy. Remove the sanding dust. Fill any cracks and holes with Presto filler and sand the dried surface. Remove the sanding dust. Before finishing, prime the surface with e.g. Varma primer, if necessary.

Painting

Stir Mute paint well before use and thin with water, if necessary. Apply 1–2 coats by roller, brush or spray.

Cleaning of tools

Clean tools with water. Tikkurila Pensselipesu Tool Cleaner is recommended to remove slightly hardened paint.

Maintenance instructions

If needed, after approx. 1 month from treating the surface, at the earliest. The surfaces are cleaned with a dry brush or dust towel. Dirty surfaces are cleaned with a damp cleaning tool moistened in a neutral (pH 6–8) washing solution. The surface may not remain wet after cleaning. Follow the dilution instructions given by the detergent manufacturer when mixing the cleaning solution.

The product achieves its final hardness and durability after one month under normal conditions, and therefore the surfaces must be handled with care during this time. If the surfaces need to be cleaned soon after finishing, clean them lightly with a dry or damp cleaning cloth.

Please note that white fingermarks may appear on dark surfaces. Marks can be gently removed by damp cloth.

Maintenance treatment

Surfaces painted with Mute interior paint can be maintenance painted with the same or similar water-borne paint. See Pretreatment.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.